



Federal Aviation Administration

Memorandum

Date: 20 OCT 2008
To: Manager, National Flight Procedures Group, AJW-32
From: *FC* Manager, Flight Technologies and Procedures Division, AFS-400
Prepared by: Flight Procedure Implementation & Oversight Branch, AFS-460
Subject: Approval Request; AJW-325 Memorandum Dated 09/25/2008

Your request to utilize a 2.75 degree glide path angle at Seattle-Tacoma Intl, Seattle, WA "ILS OR LOC RWY 34R, AMDT 1 and ILS RWY 34R (CAT II)" was discussed at Flight Standards' Procedure Review Board (PRB) meeting on October 16, 2008 and is approved.

Please direct all inquiries to Gary Powell, AFS-460, at (405) 954-9359.

Attachments

cc:
ANM-230/AJW-327
AFS-400/410/420/440/460

ILS OR LOC RWY 34R, ILS RWY 34R (CAT II), SEATTLE-TACOMA INTL
SEATTLE, WA

Glidepath angle is below the optimum glidepath of 3°. AFS-420 memo dated 12/05/2005.

The commissioned ILS glide slope angle for RWY 34R is 2.75° and there are procedures currently built and being amended for this angle. If the glide slope antenna remains at its current location, the TCH will be 65.16ft if the slope is raised to 3°; which is out of tolerance. The airport does not currently have the time or the money to relocate the glide slope antenna to be able to raise the glide path up to 3°. In the interest of aviation/commerce, request of AFS approval to retain the 2.75° glide slope.



Federal Aviation Administration

Memorandum

SEP 25 2008

Date:

To: Manager, Flight Technologies and Procedures Division
THRU: Manager, Flight Procedure Implementation & Oversight Branch

From: Thomas L. Lattimer
Manager, National Flight Procedures Group

Reply To Attn Of: Larry Strout:
(405) 954-7370
FAX (405) 954-1301

Subject: ACTION: Approval Request

ILS OR LOC RWY 34R, ILS RWY 34R (CAT II), SEATTLE-TACOMA INTL, SEATTLE, WA

Glide path angle is below the optimum glide path of 3°. AFS-420 memo dated 12/05/2005.

The commissioned ILS glide slope angle for RWY 34R is 2.75° and there are procedures currently built and being amended for this angle. If the glide slope antenna remains at its current location, the TCH will be 65.16ft if the slope is raised to 3°; which is out of tolerance. The airport does not currently have the time or the money to relocate the glide slope antenna to be able to raise the glide path up to 3°. In the interest of aviation/commerce, request of AFS approval to retain the 2.75° glide slope.

Please respond no later than: 26 November 2008

Attachments

CONCURRENCES
ROUTING SYMBOL AVN-102
INITIALS/SIG SD
DATE 9/24/08
ROUTING SYMBOL AVN-130-SPRC
INITIALS/SIG
DATE
ROUTING SYMBOL AVN-130-LEAD
INITIALS/SIG
DATE
ROUTING SYMBOL AVN-130-MGR
INITIALS/SIG DES
DATE 9/24/08
ROUTING SYMBOL AVN-102 - LEA
INITIALS/SIG CHJ
DATE 9/24/08
ROUTING SYMBOL AVN-102-FTP
INITIALS/SIG
DATE
ROUTING SYMBOL
INITIALS/SIG
DATE
ROUTING SYMBOL
INITIALS/SIG
DATE

DO NOT
REMOVE



Federal Aviation Administration

Memorandum

Date: 20 OCT 2008
To: Manager, National Flight Procedures Group, AJW-32
From: For Manager, Flight Technologies and Procedures Division, AFS-400
Prepared by: Flight Procedure Implementation & Oversight Branch, AFS-460
Subject: Approval Request; AJW-325 Memorandum Dated 09/25/2008

Your request to utilize a 2.75 degree glide path angle at Seattle-Tacoma Intl, Seattle, WA "ILS OR LOC RWY 34R, AMDT 1 and ILS RWY 34R (CAT II)" was discussed at Flight Standards' Procedure Review Board (PRB) meeting on October 16, 2008 and is approved.

Please direct all inquiries to Gary Powell, AFS-460, at (405) 954-9359.

Attachments

cc:
ANM-230/AJW-327
AFS-400/410/420/440/460